

Quest® NetVault® Backup Plug-in *for MySQL* 11.4 Release Notes

August 2017

These release notes provide information about the Quest® NetVault® Backup Plug-in *for MySQL* release.

Topics:

- [About this release](#)
- [New features](#)
- [Enhancements](#)
- [Resolved issues](#)
- [Known issues](#)
- [System requirements](#)
- [Product licensing](#)
- [Upgrade and installation instructions](#)
- [More resources](#)
- [Globalization](#)
- [About us](#)

About this release

Quest NetVault Backup (NetVault Backup) Plug-in *for MySQL* (Plug-in *for MySQL*) 11.4 is a minor release, with enhanced features and functionality. For complete product documentation, visit <https://support.quest.com/technical-documents>.

New features

New feature in NetVault Backup Plug-in *for MySQL* 11.4:

- Added support for Windows Server 2016. (DNMYSQL-368)
- Updated the plug-in to include MySQL Views in the backup process. (DNMYSQL-369)

Enhancements

The following is a list of enhancements implemented in NetVault Backup Plug-in for MySQL 11.4.

Table 1. General enhancements

Enhancement	Issue ID
Added an option for performing Transportable Tablespace (TTS) Backups.	DNMYSQL-380
Added an option for renaming a single table during restore of a TTS Backup.	DNMYSQL-304

Resolved issues

The following is a list of issues addressed in this release.

Table 2. General resolved issues

Resolved issue	Issue ID
Corrected an issue that displayed the Lock All Tables with Read Access During Backup to Prevent Loss of Transactions option as selected even when the option did not apply to the task. If the option does not apply to the task, it is displayed as disabled.	DNMYSQL-310

Known issues

The following is a list of issues, including issues attributed to third-party products, known to exist at the time of release.

Table 3. General known issues

Known issue	Issue ID
The plug-in name has been changed to use the "Plug-in for <product>" naming convention, that is, Plug-in for MySQL. If you upgrade the plug-in for a system that is managed by NetVault Backup Server 9.2, a consequence of the name change is that savesets created with the upgraded plug-in are not displayed in the NVBU Restore window when the Selection Method is set to Plugin ; only savesets created with an earlier version are displayed. Workaround for NetVault Backup Server 9.2: On the Selections tab of the NVBU Restore window, select Job in the Selection Method list to view savesets or backups created with a previous version or the upgraded plug-in. This issue was corrected in NetVault Backup 10.0.	NVBU-8267 (23470)
Due to MySQL bug 69953 , performing a restore to MySQL Server 5.5 or 5.6 fails to drop the existing slow_log table in the mysql database if MySQL logging is enabled. Therefore, the restore also fails to restore the same table. If the slow_log table is critical to your environment, re-create the slow_log table manually after the restore job completes. This issue is corrected in MySQL 5.7.	DNMYSQL-319 (30852)
Because backup data is streamed from the MySQL Server directly to the NetVault Backup Media Manager, use of special characters in database names might be interpreted as a sequence command, which affects the integrity of the backup data. Workaround: To avoid potential issues, do not use the following characters in database names: \$ ^ = @ # % +	DNMYSQL-379

Table 4. MySQL Standard/Community known issues

Known issue	Issue ID
<p>Default setting of lower_case_table_names system variable affects MySQL behavior on Mac OS X: The inconsistent behavior of case-sensitivity of MySQL on Mac OS X platforms affects the ability of the plug-in to restore backups. To ensure that you accommodate this inconsistency, be aware of the following when using the plug-in with Mac OS X:</p> <ul style="list-style-type: none"> • If the lower_case_table_names system variable is set to 1, Incremental Restores work correctly for databases that were created using lowercase, uppercase, or mixed-case names. Also, the database names are displayed in the NetVault Backup Console using lowercase letters regardless of how the actual names were created. • If the lower_case_table_names system variable is set to 2, <i>the default setting on Mac OS X</i>, Incremental Restores only work correctly for databases that were created using lowercase names. Also, the database names are displayed in the NetVault Backup Console using the same format with which they were created. <p>If you change the value of the <code>lower_case_table_names</code> system variable, stop and restart the MySQL Server to ensure that the change is implemented. For more information about this MySQL-related issue, see: http://dev.mysql.com/doc/refman/5.0/en/identifier-case-sensitivity.html</p>	DNMYSQL-133 (18430, MYG-235)
<p>Selecting Enable MySQL Replication but not configuring replication causes backups to fail: If you select the Enable MySQL Replication check box on the Configure dialog box but do not configure replication, backups fail. To correct this issue, either clear the Enable MySQL Replication check box on the Configure dialog box or set up replication and run the backup job again.</p>	DNMYSQL-241 (21629)

Table 5. MySQL Enterprise Backup (MEB) known issues

Known issue	Issue ID
<p>Under certain conditions, all InnoDB tables are backed up: All InnoDB tables in a MySQL instance are backed up if either of the following conditions is met:</p> <ol style="list-style-type: none"> 1 Only tables are explicitly selected for backup, and none of the tables are of type or storage engine InnoDB. Example: You have a MySQL Instance with two databases (DB1 and DB2). Each database contains two tables: DB1 has T1_InnoDB and T1_MyISAM and DB2 has T2_InnoDB and T2_MyISAM. If you back up T1_MyISAM and T2_MyISAM, T1_InnoDB and T2_InnoDB are also backed up. If you include one of the InnoDB tables, only that InnoDB table is backed up. If you select one of the databases, only the tables in the database are backed up. 2 Some or all databases are selected for backup and all associated InnoDB tables are excluded from the backup. Example: You have a MySQL Instance with two databases (DB1 and DB2). Each database contains two tables: DB1 has T1_InnoDB and T1_MyISAM and DB2 has T2_InnoDB and T2_MyISAM. If you back up DB1 and DB2 and exclude T1_InnoDB and T2_InnoDB, T1_InnoDB and T2_InnoDB are also backed up. If you exclude only one of the two InnoDB tables, only the other InnoDB table is backed up. <p>This behavior reflects current MEB (mysqlbackup utility) behavior, which might change in a future release (post-3.8.1).</p>	DNMYSQL-275 (22383)
<p>The plug-in does not support use of versions 3.12 and 4.0 of the MEB-based method in a clustered environment. You can only use these versions in a standalone environment.</p>	DNMYSQL-363 (32199)

System requirements

Before installing Plug-in for MySQL 11.4, ensure that your system meets the requirements outlined in the *Quest NetVault Backup Compatibility Guide* available at <https://support.quest.com/technical-documents>.

Upgrade and compatibility

- Plug-in for MySQL 11.4 requires NetVault Backup 10.0 or later. For complete supported-platform information, see the *Quest NetVault Backup Compatibility Guide*.
- **Upgrades and new installs of MySQL:** As explained in bug 68807 for MySQL, <http://bugs.mysql.com/bug.php?id=68807>, `mysql_install_db` ignores `/etc/my.cnf` in MySQL 5.6. Because MySQL 5.6 creates InnoDB statistic tables (`slave_master_info`, `mysql/slave_relay_log_info`, `innodb_index_stats`, `innodb_table_stats`, and `slave_worker_info`) and adds them to the installation directory (`basedir`) of MySQL, you might encounter a conflict with the `innodb_data_file_path = ibdata1:2000M;ibdata2:10M:autoextend` option contained in the “`my.cnf`” file. The `file_path` option places the InnoDB files one directory level higher than the `basedir`, which can cause the following error to be displayed in the MySQL error log:

```
"[Warning] InnoDB: Cannot open table mysql/slave_master_info from the internal data dictionary of InnoDB though the .frm file for the table exists. See http://dev.mysql.com/doc/refman/5.6/en/innodb-troubleshooting.html for how you can resolve the problem."
```

Until you address this error, the plug-in cannot browse the main MySQL database, and the following error is displayed: "Failed to fetch row from query result: showtable status like 'innodb_index_stats'"

It can also cause backup jobs to stop responding.

Because this option originated from a recommended sample “`my.cnf`” file for an earlier version of MySQL, this issue usually occurs on upgrades or new installs that retained the earlier version of the “`my.cnf`” file. Quest recommends that you do not use the `file_path` option on new installations and that you move the `ibdata` files to `basedir` for upgrades. For assistance, contact MySQL Support. (22367)

- **Upgrades from NetVault Backup Server from 9.2:** If you upgrade your NetVault Backup Server from 9.2 to 10.x or later, the settings you configured for error conditions encountered by the Plug-in for MySQL are returned to their defaults. If you modified the settings for error conditions encountered by the plug-in, Quest recommends that you reinstall the plug-in, reconfigure its settings, and re-create MySQL backup jobs.

Product licensing

To obtain the license key for your NetVault Backup Server environment, determine the NetVault Machine ID of your main NetVault Backup Server. Also identify the machine IDs of any clients running application plug-ins, such as Oracle, MySQL, PostgreSQL, SQL Server, and Exchange.

You can use the NetVault Configuration Wizard to install the product license keys. Alternatively, you can install the license keys from the Manage Clients page.

- [Obtaining a machine ID](#)
- [Installing a license key using the configuration wizard](#)
- [Installing a license key from the Manage Clients page](#)

Obtaining a machine ID

- 1 Start the NetVault Backup WebUI.
- 2 In the Navigation pane, click **Manage Clients**.
- 3 In the **NetVault Backup Clients** list, select the applicable machine, and click **Manage**.
- 4 On the **View Client** page, note the machine ID exactly as it is displayed in the **Client Summary** table.

Installing a license key using the configuration wizard

- 1 In the Navigation pane, click **Guided Configuration**.
- 2 On the **NetVault Configuration Wizard** page, click **Install Licenses**.
- 3 In the **NetVault Backup Clients** list, select the applicable machine, and click **Next**.
- 4 In the **Enter the license key string** box, type or copy and paste the license key, and click **Apply**.
After the key is applied successfully, a message is displayed.

Installing a license key from the Manage Clients page

- 1 In the Navigation pane, click **Manage Clients**.
- 2 In the **NetVault Backup Clients** list, select the applicable machine, and click **Manage**.
- 3 On the **View Client** page, click **Install License**.
- 4 In the **Install License** dialog box, type or copy and paste the license key, and click **Apply**.
After the key is applied successfully, a message is displayed.
- 5 To dismiss the dialog box, click **Close**.

Upgrade and installation instructions

For upgrade and installation instructions, see the *Quest NetVault Backup Plug-in for MySQL User's Guide*.

- i** **IMPORTANT:** Due to the plug-in name change, **you must remove the existing plug-in before you install the new version if you are using a version before 4.4**. This process ensures that items with the previous plug-in name are removed before items with the new name are installed.

More resources

Additional information is available from the following:

- [Online product documentation](#)
- [NetVault community](#)

Globalization

This section contains information about installing and operating this product in non-English configurations, such as those needed by customers outside of North America. This section does not replace the materials about supported platforms and configurations found elsewhere in the product documentation.

This release supports any single-byte or multi-byte character set. In this release, all product components should be configured to use the same or compatible character encodings and should be installed to use the same locale and regional options. This release is targeted to support operations in the following regions: North America, Western Europe and Latin America, Central and Eastern Europe, Far-East Asia, Japan. It supports bidirectional writing (Arabic and Hebrew).

The release is localized to the following languages: Chinese (Simplified), French, German, Japanese, Korean.

About us

We are more than just a name

We are on a quest to make your information technology work harder for you. That is why we build community-driven software solutions that help you spend less time on IT administration and more time on business innovation. We help you modernize your data center, get you to the cloud quicker and provide the expertise, security and accessibility you need to grow your data-driven business. Combined with Quest's invitation to the global community to be a part of its innovation, and our firm commitment to ensuring customer satisfaction, we continue to deliver solutions that have a real impact on our customers today and leave a legacy we are proud of. We are challenging the status quo by transforming into a new software company. And as your partner, we work tirelessly to make sure your information technology is designed for you and by you. This is our mission, and we are in this together. Welcome to a new Quest. You are invited to Join the Innovation™.

Our brand, our vision. Together.

Our logo reflects our story: innovation, community and support. An important part of this story begins with the letter Q. It is a perfect circle, representing our commitment to technological precision and strength. The space in the Q itself symbolizes our need to add the missing piece—you—to the community, to the new Quest.

Contacting Quest

For sales or other inquiries, visit www.quest.com.

Technical support resources

Technical support is available to Quest customers with a valid maintenance contract and customers who have trial versions. You can access the Quest Support Portal at <https://support.quest.com>.

The Support Portal provides self-help tools you can use to solve problems quickly and independently, 24 hours a day, 365 days a year. The Support Portal enables you to:

- Submit and manage a Service Request.
- View Knowledge Base articles.
- Sign up for product notifications.
- Download software and technical documentation.
- View how-to-videos.
- Engage in community discussions.
- Chat with support engineers online.
- View services to assist you with your product.

© 2017 Quest Software Inc.

ALL RIGHTS RESERVED.

This guide contains proprietary information protected by copyright. The software described in this guide is furnished under a software license or nondisclosure agreement. This software may be used or copied only in accordance with the terms of the applicable agreement. No part of this guide may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of Quest Software Inc.

The information in this document is provided in connection with Quest Software products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Quest Software products. EXCEPT AS SET FORTH IN THE TERMS AND CONDITIONS AS SPECIFIED IN THE LICENSE AGREEMENT FOR THIS PRODUCT, QUEST SOFTWARE ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL QUEST SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF QUEST SOFTWARE HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Quest Software makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Quest Software does not make any commitment to update the information contained in this document.

If you have any questions regarding your potential use of this material, contact:

Quest Software Inc.
Attn: LEGAL Dept.
4 Polaris Way
Aliso Viejo, CA 92656

Refer to our website (<https://www.quest.com>) for regional and international office information.


Patents


Quest Software is proud of our advanced technology. Patents and pending patents may apply to this product. For the most current information about applicable patents for this product, please visit our website at <https://www.quest.com/legal>.


Trademarks

Quest, the Quest logo, Join the Innovation, and NetVault are trademarks and registered trademarks of Quest Software Inc. For a complete list of Quest marks, visit <https://www.quest.com/legal/trademark-information.aspx>. All other trademarks and registered trademarks are property of their respective owners.

Legend

-  **WARNING:** A WARNING icon indicates a potential for property damage, personal injury, or death.

-  **CAUTION:** A CAUTION icon indicates potential damage to hardware or loss of data if instructions are not followed.

-  **IMPORTANT NOTE, NOTE, TIP, MOBILE, or VIDEO:** An information icon indicates supporting information.